

## WPV Silent-Line



## Capaciteits info

Type model	Capaciteit (t°=-5°C)				Luchtstroom				geluidsvermogeniveau				geluidsdrukniveau			oppervlakte
	DT1=7K		R407 C		m3/h				dB(A)*				dB(A)			m2
WPV	kW															
HL 050/1-0875-2	3,2	5	6,1	6,7	1690	3600	5330	6410	47	60	70	75	26	38	48	53
HL 050/1-0875-3	4,6	7	8,2	8,8	1640	3500	5180	6230	47	60	70	75	26	38	48	53
HL 050/1-0875-4	4,8	8,3	10,6	11,8	1560	3330	4930	5940	47	60	70	75	26	38	48	53
HL 050/2-1800-3	9	14,5	17,8	19,5	3330	7110	10520	12650	50	63	73	78	29	41	51	56
HL 050/2-1800-4	10,2	17,1	21,6	23,8	3120	6670	9870	11870	50	63	73	78	29	41	51	56
HL 050/3-2725-3	14,1	22,1	27,1	29,4	5070	10820	16010	19260	52	65	75	80	31	43	53	58
HL 050/3-2725-4	13,5	23,3	30,2	33,8	4680	10000	14800	17810	52	65	75	80	31	43	53	58

## Afmetingen

